

CONSTRUCTION SPECIFICATIONS FOR SANITARY SEWER (CONTINUED)

9. THE CONTRACTOR SHALL SUBMIT AN APPROVED TRAFFIC CONTROL PLAN. INSIDE THE CITY THIS PLAN SHALL BE APPROVED BY THE PUBLIC WORKS DEPARTMENT (835-2662) AND OUTSIDE THE CITY IS SHALL BE APPROVED BY THE CLARK COUNTY TRAFFIC ENGINEER (699-2375). APPROVAL SHALL BE OBTAINED PRIOR TO BEGINNING CONSTRUCTION.
10. COMPLETE TAPS TO EXISTING SEWERLINES WITH MANHOLES. AFTER EXPOSING THE EXISTING SEWER LINES, CONSTRUCT CAST IN PLACE BASE PER PRECAST CONCRETE MANHOLE DETAILS. ONLY AFTER THE BASE HAS ADEQUATELY SET UP, PER CITY INSPECTOR'S APPROVAL MAY THE RISER SECTIONS BE INSTALLED. ANY VARIATIONS TO BE APPROVED BY CITY.
11. NO EXCAVATED MATERIAL WILL BE PLACED ON CITY STREETS WITHOUT PRIOR APPROVAL. NO DITCH IS TO BE LEFT OPEN.
12. ALL SEWERS ARE TO BE AIR TESTED AND A MANDREL PULLED TO ASSURE ROUNDNESS OF PIPE. TV-ING SEWER PIPE WILL BE REQUIRED PRIOR TO ACCEPTANCE OF WORK. MANHOLES WILL BE VACUUM TESTED AFTER PAVING.
13. GROUT AND CHANNEL ONE MANHOLE FOR CITY INSPECTION. IF FINISHED MANHOLE IS APPROVED BY CITY INSPECTORS THE REST OF THE MANHOLES CAN BE COMPLETED.