



### POST MOUNTING SOCKET

#### NOTES:

1. HOT DIP GALVANIZE AFTER FABRICATION. STANDARD 2" WELDED STEEL PIPE SHALL CONFORM TO THE ASTM 'SPECIFICATIONS FOR WELDED STEEL PIPE' A120 AND A123 FOR GALVANIZING.
2. ALL PIPE SHALL BE CAPPED AS APPROVED BY ENGINEER WHEN STREET NAME SIGNS ARE NOT REQUIRED.
3. 7' IS MINIMUM HEIGHT TO BOTTOM OF LOWER SIGN IN URBAN AREAS. 8' IS MINIMUM HEIGHT WHEN SIGNS ARE PLACED ABOVE A BIKE PATH.
4. EDGE OF SIGN SHALL NOT BE PLACED CLOSER THAN 2' TO THE FACE OF CURB.
5. V-LOCK INSTALLATION TYPES:  
CONCRETE: VR1  
ASPHALT/EARTH: VR2  
SOFT SOIL: VR3
6. STREET NAME SIGNS SHALL BE D3-102 WITH A 6" WHITE ALL CAPITAL REFLECTIVE LEGEND ON A GREEN REFLECTIVE BACKGROUND. SIGNS SHALL BE CONSTRUCTED ON EXTRUDED BLADE ALUMINUM AND MEET THE REQUIREMENTS OF WSDOT STANDARD SPECIFICATION 9-28.

### PIPE SIGN SUPPORT DETAIL WITH POST MOUNTING SOCKET

### SIGN DETAIL

NTS